

# STRUCTURAL DESIGN OF *mortarless* WALLS to AS 3600 : 2009

## DESIGN MANUAL - Part 2b

Warwick Colefax BE(Hons) DipTechEng(Struct) MIEAust CPEng RPEQ

# 200 mortarless (design tables) CHAMFERED

In this mortarless Design Manual Part 2a design tables and diagrams are provided for combinations of block grades (unconfined compressive strengths) and core fill grout strengths (28 day cylinder strengths) as follows:

**BLOCK GRADES:** 15 & 20 MPa  
**CORE FILL CONCRETE (GROUT):** 20MPa

### AVAILABILITY:

The 200 *mortarless* masonry units to which these design tables apply are available in the following regions:

Australia (Austral Pronto Block, TCB Mortarless)  
Middle East (Oman, UAE)  
Asia (India)

Prior to specifying 200 *mortarless* check proximity of nearest supplier with local Licensee.

### DISCLAIMER:

This *mortarless* Design Manual has been compiled to assist structural engineers quickly and efficiently prepare designs and details of load-bearing *mortarless* masonry structures and elements. Numerous design tables and diagrams have been provided and these cover a broad range of typical design applications. While every care has been taken to ensure the information provided is accurate and complete for the design situations and actions covered, the information should only be used by experienced practising structural engineers, and all engineers should familiarise themselves with the full contents of the applicable Standards to ensure no requirement is overlooked. Mortarless Pty Ltd, its licensees and the author accept no liability whatsoever arising out of the use or misuse of the information provided in this design manual.

## Contents:

### ► **SECTION 1. 200 mortarless MASONRY UNITS**

Cross section dimensions and properties

### ► **SECTION 2. DESIGN OF WALLS FOR AXIAL COMPRESSION**

#### **Design Procedure – Axial compression**

Calculation of effective eccentricity – simplified design method – one-way buckling

**Table W1-200U:** 15MPa blocks, 20MPa grout,  $k=0.75$

**Table W2-200U:** 20MPa blocks, 20MPa grout,  $k=0.75$

**Table W3-200U:** 15MPa blocks, 20MPa grout,  $k=1.0$

**Table W4-200U:** 20MPa blocks, 20MPa grout,  $k=1.0$

**Diagram 2-1:** Effective height factor  $k$  for walls with two-way buckling

**Table W5-200U:** 15MPa blocks, 20MPa grout, two way buckling

**Table W6-200U:** 20MPa blocks, 20MPa grout, two way buckling

### ► **SECTION 3. DESIGN OF WALLS FOR BENDING**

Reinforcing bar positions

#### **Design Procedure – Out-of-plane bending**

**Table 3.1:** Bending moment capacities (vertical and horizontal)

**Table 3.2:** Design bending moment capacity of mortarless beams – 15MPa

**Table 3.3:** Design bending moment capacity of mortarless beams – 20MPa

### ► **SECTION 4. DESIGN OF WALLS FOR COMBINED BENDING AND COMPRESSION**

#### **Design Procedure – Combined bending and compression**

**Diagram 4-1:** Interaction Diagram -  $f'_c = 15\text{MPa}$

**Diagram 4-2:** Interaction Diagram -  $f'_c = 20\text{MPa}$

### ► **SECTION 5. DESIGN OF WALLS FOR SHEAR**

#### **Design Procedure – Shear**

**Diagram 5-1:** In-plane shear strength of shear walls – excluding contribution of reinforcement

**Diagram 5-2:** Contribution of reinforcement to in-plane shear strength of shear walls

**Diagram 5-3:** Out-of-plane shear capacity – 15MPa blocks, vertical bars in V1 position

**Diagram 5-4:** Out-of-plane shear capacity – 15MPa blocks, vertical bars in V2 position

**Diagram 5-5:** Out-of-plane shear capacity – 20MPa blocks, vertical bars in V1 position

**Diagram 5-6:** Out-of-plane shear capacity – 20MPa blocks, vertical bars in V2 position

**Table 5.1:** Shear capacities mortarless beams without shear reinforcement

**Table 5.2:** Shear capacities mortarless beams with shear reinforcement